Schnitt-Griffy HS 950

A new generation of professional **cutting and clearing tools** providing maximum safety in one work step!















Technical Specifications

L x W x H: 2,200 x 1,000 x 1,250 mm Weight without attachment: approx. 1075 kg

Opening width: approx. 660 mm Cutting performance: alder approx. 380 mm, oak approx. 280 mm Pivoting angle: ca. 2 x 70° Torque: at 70°: 15 kNm, at 35°: 18 kNm, at 0°: 23 kNm Connection main working circuit:

1 x double-action, pressure 300 bar, oil flow 100 to 160 l/min (Primary and secondary safety switch necessary!) Connection swivel unit: 1 x double-action, pressure 200 bar, oil flow 20 to 40 l/min (Primary and secondary safety switch necessary!) Recommended excavator size: Fifteen tons or greater Minimum lifting capacity (mass): 2.5 tons Technical modifications reserved

HA MAS Ziegel D-363 Tel.: + Fax: +

HANS HABBIG MASCHINENBAU Ziegelhütte 1

D-36381 Schlüchtern Tel.: +49 6661 71347 Fax: +49 6661 5922 info@hans-habbig.com www.hans-habbig.com

The Schnitt-Griffy

attached to a CAT 316C mobile excavator. Protected from rain and frost, the excavator's driver can process the wood in a convenient manner. Thanks to its double pair of grippers, our latest **HS 950** model provides an even greater level of safety during operation.

Our **HS 950 Schnitt-Griffy** comes standard with a swivel unit. The pivoting angle of $2 \times 70^{\circ}$ makes it possible to cut off branches with even greater accuracy. The machine also allows you to deposit the cut wood next to the excavator, for example, by the side of the road. This way, the cut wood can be picked up more easily by a wood chopper.

The device can be used for a wide variety of applications: on the road, by the side of rivers, in the forest, for landscaping and landscape conservation, for Common Osiers (willow trees), on railways, for overland power lines, and much more.

The timbers are inevitably embraced by two crossing knives and held securely during cutting by the 5 gripper arms. This will allow you to deposit the cut wood exactly where you want it to be.

Cross section



Distributed by: