# Schnitt-Griffy HS 865 SE



## The New Generation Schnitt-Griffy





4 gripper arms. By individually mounted grippers and a serrated frame fixation the holding power is greater than previously and thus your safety is significantly improved.

A hydraulic valve controls the grippers so that they close before cutting and keep the clippings safely. The cut

The **HS 865 SE** is a handy and robust cutter with double grippers. The timbers are inevitably embraced by two crossing knives and held securely during cutting by the

The **Schnitt-Griffy HS 865 SE** and **HS 865** is a more powerful variant of our model HS 860.



A hydraulic valve controls the grippers so that they close before cutting and keep the clippings safely. The cut wood can then be deposited exactly where you want it to be.



As carrier vehicles wheel excavators and crawler excavators have proved particularly useful.

Our **Schnitt-Griffy HS 865 SE** comes standard with a swivel unit. The pivoting angle of 2 x 60° makes it possible to cut off branches accurately and to deposit the clippings along the excavator's side as well.



The model  ${f HS~865}$  without swivel unit is available on request.

## Applications:

On the road, by the side of rivers, in the forest, for landscaping and landscape conservation, for Common Osiers (willow trees), on railways, for overland power lines, and much more.



#### TECHNICAL SPECIFICATIONS

**Length**  $\times$  **Width**  $\times$  **Height:** . . . . . . . . . 1,700  $\times$  800  $\times$  1,150 mm

Weigth without attachment: . . . . . . . . . . approx. 795 kg (approx. 720 kg without SE)

**Opening width:** . . . . . . . . . . . . . . . approx. 660 mm

Cutting performance: . . . . . . . . . . . alder approx. 320 mm, oak approx. 230 mm

Pivoting angle: . . . . . . . . . . . . . . approx. 2 x 60°

**Torque:** . . . . . . . . . . . . . . . . . . at 0°: 30 kNm, at 60°: 15 kNm

Connection main working circuit: . . . . . . . 1 x double-action, pressure 300 bar, oil flow 100 to 110 l/min

(Primary and secondary safety switch necessary!)

**Recommended excavator size:**  $\dots \dots 11-18$  to

Minimum lifting capacity (mass): . . . . . . . 1.6 to

Technical modifications reserved



### HANS HABBIG MASCHINENBAU Ziegelhütte 1

Ziegelhütte 1 D-36381 Schlüchtern Tel.: +49 6661 71347 Fax: +49 6661 5922 info@hans-habbig.com www.hans-habbig.com Distribution by: